



Cal/OSHA, DOT HAZMAT, EEOC, EPA, HAZWOPER, HIPAA, IATA, IMDG, TDG, MSHA, OSHA, and Canada OHS Regulations and Safety Online Training

Since 2008

**This document is provided as a training aid
and may not reflect current laws and regulations.**

Be sure and consult with the appropriate governing agencies
or publication providers listed in the "Resources" section of our website.

www.ComplianceTrainingOnline.com



[Facebook](#)



[LinkedIn](#)



[Twitter](#)



[Website](#)

Dipping and Coating Operations (Dip Tanks)

Chapter 296-835 WAC

Resources

Helpful Tools

Dip Tanks PPE Selection Tool R-1

Resources



Dip Tank PPE Selection Tool

Chapter 296-835 WAC

Resources

This tool can be used with the Hazard Assessment required by the Safety and Health Core Rules, Chapter 296-800 WAC, which requires you to select appropriate personal protective equipment (PPE). The table lists examples of PPE that can be used to protect employees from the hazards of dipping and coating operations.

Hazard	PPE to Consider
Employees' feet become wet with dip tank liquid	<ul style="list-style-type: none">Shoes or boots of rubber or other material that can't be penetrated by dip tank liquidRubber overshoesWooden soled shoes
Employees handle work wet with dip tank liquid	<ul style="list-style-type: none">Gloves¹ long enough to keep liquid from entering through the top of the gloves
Employees' clothing may get wet with dip tank liquid Employees' clothing may get wet with dip tank liquid where small parts are cleaned, plated, or acid dipped in open tanks and rapid production work is required	<ul style="list-style-type: none">Aprons²CoatsJacketsSleeves <p>Any of the previous methods or:</p> <ul style="list-style-type: none">Cotton clothing, shoes or short boots, and an apron
Dip tank liquid may splash and cause damage to the eyes or face Note: This includes manually adding or removing chemicals from the tank.	<ul style="list-style-type: none">Tight-fitting chemical gogglesEffective face shield

¹PPE selected has to be made of rubber or other material the dip tank liquid can't penetrate. Some materials can provide protection for a limited time, but needs to be replaced at intervals to maintain continuous employee protection.

²Aprons should be long enough to keep liquid from entering the top of the employees' boots or shoes.

